

Nev'n's

BAKERY MACHINES

An Innovative Solution to Bake
It's always NEVIN'S



Planetary Mixer



Accessories



SPECIFICATIONS

MODEL	NHM - P40	NHM - P60	NHM - P100	NHM - P150
Capacity	40 Ltr.	60 Ltr.	100 Ltr.	150 Ltr
Batter Capacity	16 kgs	24 kgs	40 kgs	60 kgs
Motor HP	3	4	5	8.5
Motor Phase	3 Ø / 1Ø	3Ø	3Ø	3Ø

- Low Noise & no heating of batter
- Variable Speed adjuster
- Timer for uniformity of batches

Spiral Kneader



SPECIFICATIONS

MODEL	NHM-S 50	NHM-S 100	NHM-S 150 T	NHM-S 160 HD
Flour Capacity	30 kg	60 kg	90 kg	100 kg
Power	3 HP	9 HP	12 HP	15 HP
Dimension	1150 x 600 x 1100	1320 x 820 x 1480	1450 x 975 x 1580	2085 x 1120 x 1552
Tipper	—	Optional	Optional	Optional

- Dough doesn't get heated up
- Shorter mixing time
- Safety guard for protection
- Tilting model option available

Volumetric Divider

SPECIFICATIONS

MODEL	WEIGHT RANGE	PISTON	POWER	HOPPER CAPACITY
NHM - 120	100 - 1000gm	120mm	3.0 HP	120 kg

- This divides the dough into the desired weight and then rounds it
- High accuracy for consistency of piece
- Suitable for continuous operation with soft / medium / hard dough



Dough Sheeter



SPECIFICATIONS

MODEL	: NHM-TT-SS
Dimension	: 2000 x 1130 x 800 mm (L x Bx H)
Power	: 1 HP / 3 PHASE
Body	: MS Finish Powder Coating
Roller Length	: 540 mm
Opening of Roller cap	: 0.5 - 34 mm

- Easy to use features
- It can work every type of dough even to very minimum thickness
- Cylinder guards with safety mico switch

SPECIFICATIONS

MODEL	: NHM- DS600
Belt Dimension	: 580 x 2860 mm
Roller Dimension	: 600 mm (L)
Roller to Roller Height	: Max. 34 mm, Min. 1 mm
Power	: 1 HP
Overall Dimension	: 3300 x 1200 x 1350 mm (LxBxH)

Table top Dough Sheeter



Dough Moulder



SPECIFICATIONS

MODEL	MINI MOULDER	MAXI MOULDER
Capacity - pc/hr	2000	3000
Dimensions	1420 x660x1200	2525x850x1500
Power	0.5 HP	1.0 HP
Weight of Dough	100 - 800 gm	200 - 1000 gm

- Easy to use features
- It can work every type of dough even to very minimum thickness
- Cylinder guards with safety micro switch

Rusk Laying Machine

SPECIFICATIONS

MODEL	: NHM - L-10
Capacity	: 10 Tray Min
Power	: 2HP
Tray Size	: As per your size
Reqd Labour	: 4 nos
Size in feet	: 3 feet W x17 feet L x 5 feet H



Table Top Bread Slicer



SPECIFICATIONS

Model	: NHM-600
Slice Width	: 10 mm / 12 mm
Max. Bread Size	: 350 mm x 125 mm (W x H)
Capacity	: 600 Loafs / hr
Power	: 0.25 HP
Dimension	: 800 x 600 x 800 (L x B x H)

SPECIFICATIONS

Model	: Industrial Slicer
Slice Width	: 10 mm / 12 mm
Max. Bread Size	: 380 mm x 120 mm (W x H)
Capacity	: 800 - 1000 Loafs / hr
Power	: 1.5 HP - 415v
Dimension	: 1980 x 1000 x 1500 (L x B x H)

Heavy Duty Slicer



SPECIFICATIONS

Model	: Heavy Duty 3000
Slice Width	: 10 mm / 12 mm
Max. Bread Size	: 470 mm x 140 mm (W x H)
Capacity	: 3000 Loafs / hr
Power	: 5.0 HP
Dimension	: 4600 x 1250 x 1300 (L x B x H)

Cake Slicer



SPECIFICATIONS

MODEL	: NHM-CS
Size	: 2.5 x 2.5 x 5.5 Ft
Power	: 0.5 HP / 3 PHASE
Control	: Drive
Slice width	: Customize


- Compact & rugged construction with minimal noise
- All food contact parts made with food grade material

Oil Spraying Machine



Application

Automatic oil spray machine can be used for moulds and lids to get a uniform coat of oil automatically thus eliminating the large labor required during manual operation. Oil spillages are avoided thus keeping the machine and work place clean. Exceptional speed to deliver @1800 trays/hour. Same machine can be used to oil moulds of different sizes.

 <https://youtu.be/yFwlibETwyM>

Salient Features:

- ▲ Advanced technology used for manufacturing the machine
- ▲ It can sprays oil uniformly to various types of mould.
- ▲ Production capacity 1800 Moulds /hr
- ▲ Oil usage will be reduced
- ▲ Save time and money
- ▲ Easy to operate, user friendly & very hygienic.
- ▲ Unskilled labour can also operate the Machine
- ▲ Requires Two unskilled labours to operate it.
- ▲ Touch Screen control for easy operation.
- ▲ Full Stainless Steel Body

Cookies Depositor (Wire Cut & Dropping)



SPECIFICATIONS

MODEL	NHM - C 400	NHM - C 450	NHM - C 500
Tray Dimension	400 x 600 mm	450 x 700 mm	500 x 700 mm
No. of Nozzles	5	6	7
Production Speed	65	65	65
Production Speed	50	50	50
Tray Conveyer	Belt	Belt	Belt
Power	2.04 HP	2.04 HP	2.04 HP
Dimension (mm)	1650 x 1260 x 1400	1650 x 1305 x 1400	1650 x 1355 x 1400

- Suitable to make variety of biscuit, cookies, cakes, muffins
- fully SS body
- Touch screen operation for ease of use
- Replacement of parts and cleaning has been made very easy and safe

Cake Depositor



Application

The qualitative range of filler offered by us is known for its durability, cost efficiency and accuracy. High grade raw materials are used to ensure smooth functioning for long uninterrupted periods. Adjustable speed as per customer requirement.

Salient Features:

- ▲ Leak proof
- ▲ High
- ▲ Fully Automatic
- ▲ Uniform Weight in all Strokes Each Nozzle
- ▲ User Friendly, Easy to handle
- ▲ Easy to clean

SPECIFICATIONS			
MODEL	PNEUMATIC SOURCE	DIMENSION (L X B X H)	CYCLES OF PRODUCTION
NHM - 6	6 Nozzles	500 x 1150 x 1700	Adjustable from 30-40 per minute

Final Proofer



SPECIFICATIONS		
MODEL	DIMENSION (L X B X H)	HEATING COIL KW
50 x 70 - 2 Trolley	1070 x 1580 x 2300	HP 7.6 kw
50 x 70 - 4 Trolley	2240 x 1620 x 2300	HP 9.6 kw
70 x 90 - 2 Trolley	1415 x 2690 x 2300	HP 9.6 kw
60 x 80 - 4 Trolley	2550 x 1850 x 2300	HP 11.6 kw
60 x 80 - 8 Trolley	2550 x 3220 x 2300	HP 15.6 kw
60 x 80 - 12 Trolley	2250 x 4800 x 2300	HP 17.4 kw

- Final proofer is used for proofing of dough once the moulding is done
- This reduces the huge waiting time that is usually needed for proofing of dough
- SS body / PUF panel option

IMPORTED MACHINES

Fully Automatic Arabic Pita Bread Line



- ▲ Machines
- ▲ Dough Divider
- ▲ Double Output
- ▲ Primary Proofer
- ▲ Dough Flattener
- ▲ Final Proofer
- ▲ Tunnel Oven
- ▲ Outfeed Roller
- ▲ Conveyor Unit
- ▲ Cooling Conveyor

Egg Breaker Machine

SPECIFICATIONS

MODEL	: NNM-EGC-02
Capacity	: 5400 eggs/hour
Power	: 300 W
Dimensions	: 1.75 x 1.15 x 0.88 m
Material	: Stainless steel
Breaking Lanes	: Double Lane
Weight	: 140 kg



Small Kitchen Equipments



Deck Oven



Planetary Mixer



Spiral Mixer



Bun Divider

Rotary Rack Oven



ROTARY RACK OVEN SPECIFICATIONS					
MODEL	DIMENSION	TRAY SIZE	POWER	BAKING AREA	BREAD / LOAD
NHM - RO - 108	1310 x 1890 x 1910	12-50 x 70	2.25 HP	4.2	108
NHM - RO - 144	1310 x 1890 x 2485	15-50 x 70	2.25 HP	5.25	144
NHM - RO - 169	1310 x 1970 x 2510	18-50 x 70	2.75 HP	6.31	168
NHM - RO - 252	1560 x 2300 x 2510	18-60 x 80	3.75 HP	8.64	252
NHM - RO - 336	1560 x 2500 x 2510	18-70 x 90	3.75 HP	11.34	336
NHM - RO - 504	2105 x 2920 x 2710	60 x 80	4.50 HP	17.28	504
NHM - RO - 672	3255 x 2465 x 2710	18-70 x 90-2	6.25 HP	22.68	672
NHM - RO - 840	3595 x 2730 x 2710	18-60 x 90-4	6.50 HP	34.56	840
NHM - RO - 1008	4080 x 3225 x 2710	18-70 x 90-4	9.0 HP	45.36	1008

- Low fuel consumption
- High quality insulators used
- High efficiency thereby reduces baking time perfect colour for bread /rusk / biscuit

NEVIN HITECH MACHINES

Head Office

352/1A, Kallikadu Thottam, Thudiyalur Road,
Saravanampatty, Coimbatore - 641 035.

Phone : 0422 - 2670066 | Mobile : +91 99406 49140

Branch Office

977-Tower, River Heights, Rajnagar Extension, Ghaziabad - 201 017.

Mob: +91 97867 10066

info@nevinhitechmachines.com | www.nevinhitechmachines.com

SOUTH ZONE : +91 99406 49140
WEST ZONE : +91 96390 00333

NORTH ZONE : +91 97867 10066
EAST ZONE : +91 81225 46308